

Sanders and polishers



77H30B106-EU



G1A200PS812



PBA416
with rotated head

Model	Free speed [rpm]	Rated power [kW]	Weight [kg]	Length [mm]	Height [mm]	Side to centre [mm]	Spindle end / belt size [inches]
STRAIGHT "ErgoPro" SANDERS							
77H50B106-EU	5000	1,10	3,3	449	---	48	5/8"-11 x 2"
77H30B106-EU	3000	1,10	3,3	449	---	48	5/8"-11 x 2"
G-SERIES BELT SANDERS							
G1A200PS812	20000	0,3	0,54	273	65	16	Belt size 13 x 305
G1A120PS812	12000	0,3	0,54	273	65	16	13 x 305
G1A120PS418	12000	0,3	0,54	356	65	16	6 x 457
PBA416	14800	0,22	1,05	---	65	---	15 x 475
VERTICAL SANDERS "7" & "ErgoPro" SERIES							
7S60L-EU	6000	0,6	2,0	178	161	30	Spindle end 5/8"-11
7S48L-EU	4800	0,6	2,0	178	161	30	5/8"-11
7S30L-EU	3000	0,6	2,0	178	161	30	5/8"-11
7S24L-EU	2400	0,6	2,0	178	161	30	5/8"-11
88S60W107-EU	6000	1,5	2,8	224	152	54	5/8"-11
88S45W107-EU	4500	1,3	2,8	224	152	54	5/8"-11
ANGLE SANDERS							
POLA15000	15000	0,22	0,65	---	90	---	Spindle end 6 mm collet
G1A200PS4M	20000	0,3	0,5	156	56	14	1/4"-20
G1A120PS4M	12000	0,3	0,5	156	56	14	1/4"-20
G2L100PS10	10000	0,6	1,77	321	65	19	5/8"-11
G3L086PS10 ¹⁾	8600	1,0	1,9	330	76	20	5/8"-11
ANGLE SANDERS "ErgoPro" SERIES							
77A60W107-EU	6000	1,1	3,5	446	78	33	Spindle end 5/8"-11
77A45W109-EU	4500	1,1	3,5	446	78	33	5/8"-11
77A25F107-EU	2500	1,1	3,8	446	78	33	5/8"-11

¹⁾ - This angle tool is suitable for both sanding wheels and the wire brushes.



7S60L-EU



88S60W107-EU



G1A200PS4M



POLA15000



G3L086PS10



77A60W107-EU



G2L100PS10

Specification at 620 kPa. Air inlet: 1/4" NPT (series 7, G1, G2, POLA & PBA), 3/8"NPT (series G3, 77), 1/2"NPT (series 88).
Recommended hose size: 10 mm (series 7, G1, G2), 13 mm (series G3, 77, POLA & PBA), 19 mm (series 88).