

Experience the power of Ingersoll Rand construction and road-building equipment, industry-leading support and service.

Whatever your job, Ingersoll Rand has the solution from pavers and compactors, portable air compressors, light towers and generators, earth-moving equipment, material handlers, concrete equipment to attachments.

Running a successful business takes more than powerful equipment. That's why Ingersoll Rand partners with an experienced global dealer network to stand beside you every step of the way.

The Promaxx™ paving breaker introduces a unique combination of features. High power output with unmatched levels of comfort and control, gives world class breaking performance everytime.

A unique patent-pending, spring loaded anvil bushing device keeps the tool firmly pressed against the work surface, whilst at the same time reducing vibration to the operator. This dramatically improves control of the unit while maintaining outstanding power.

Internal lubricator for continuous tool protection.

State-of-the-art **non-metallic materials** are used to eliminate rust and ensure consistent performance.

Unique Metallurgy – Cylinder area work – hardens as the tool is used, increasing wear resistance.

Drop-in valve cartridge simplifies maintenance and reduces overall operating cost.

One-piece breaker housing eliminates the need for side rods and springs. Fewer parts mean lower operating costs.

Patent-pending anvil bushing eliminates the need for an anvil block while delivering smooth operation, superior control, and unsurpassed, breaking power.

Four-bolt backhead is contoured to fit the operator's leg, and is easily removed for routine maintenance.

Ergonomically designed handles, grips, throttle lever and breaker housing provide **Maximum** operator comfort and productivity.

Powr-Strok™ piston cycle transfers blow energy directly to the tool.

Optional Flex-Handles unlike spring-mounted handles, this patented design flexes up and down, reducing vibration in a full 360° range of motion. The result is improved comfort and control.

A complete line of accessories is available.

Promaxx™ Specifications

Model	Net weight		Length		Bore		Stroke		Blows per min.	Recomm. hose size		Noise level dBa	Shank size	
	kg	lbs	mm	in	mm	in	mm	in		mm	in		mm	in
MX60	39	86	686	27.5	66.5	2.62	146	5.75	1250	19	3/4	-	32 x 160	1 1/4 x 6 1/4
MX90	39	86	686	27.5	66.5	2.62	146	5.75	1250	19	3/4	-	32 x 160	1 1/4 x 6 1/4

* Vibration level 23.5m/s² in accordance with BSEN 28862

Jack Hammer Specifications at 620kPa (90psi) air pressure

Model	Weight	Length	Blows per min.	Barrel bore	Pistol stroke	Max. drill	Max. drill depth	Chuck size hex with collar
	kg	mm		mm	mm	mm	mm	mm
JH40CT-EU	27.7	572	2000	-	-	51	5500	22 x108

Air consumption: JH40=56 l/sec. Models JH40 include silencers.

Distributor

www.irco.co.za



For additional information about the tools shown in this leaflet, and assistance with selection, please contact your nearest Ingersoll Rand distributor.

Gauteng (011) 864-3930 • Cape Town (021) 386-2070 • Durban (031) 705-9374