



Plate clamp model Shark

Capacity 1000 - 3000 kg

Features

- For the toughest operating conditions.
- This clamp is primarily used for transporting single steel plates in the vertical position, as well as lifting and turning through 180°, up to a surface hardness of HRC 40.
- Quality as yet unknown for plate clamps, guarantees highest safety standards and an extremely long service life.
- Fulfils the requirements of all relevant standards and EU-Directives.

Options

- Special jaws for a surface hardness up to HRC 50. Especially for alloyed / stainless steel and slippery surfaces.

The min. load is 10% of the nominal WLL!

The surface hardness of the material must not exceed HRC 40.

Technical data model Shark

Model	EAN-No. 4025092*	Capacity kg	Jaw capacity Z mm	Weight kg
Shark 1,0	*558808	1000	0 - 20	3.3
Shark 2,0	*558815	2000	0 - 32	6.8
Shark 3,0	*198110	3000	0 - 32	7.2
Shark 1,0 special	*558914	1000	0 - 20	3.3
Shark 2,0 special	*558921	2000	0 - 32	6.8
Shark 3,0 special	*197977	3000	0 - 32	7.2

Dimensions model Shark

Model	Shark 1,0	Shark 2,0	Shark 3,0	Shark 1,0 special	Shark 2,0 special	Shark 3,0 special
A, mm	120	170	170	120	170	170
B, mm	240	345	362	240	345	362
Ø C, mm	36	65	80	36	65	80
D, mm	42	58	58	42	58	58
E, mm	60	80	80	60	80	80
F, mm	72	88	88	72	88	88
G, mm	58	69	69	58	69	69
H, mm	12	15	15	12	15	15
I, mm	12	19	20	12	19	20
J, mm	137	191	191	137	191	191
K, mm	152	214	214	152	214	214
L, mm	210	302	320	210	302	320

