

## Tiger Adjustable Trolley - APT



### Main Features

- Fitted with a screw spindle which allows easy adjustment and high clamping force to the various flange sizes within its capacity
- Shackle allows for use at angles across the beam
- Designed to provide smooth and easy traversing
- The anti-drop plates design ensures extra safety, and also prevents damage to wheels when contacting end rail stoppers
- Wheels run on sealed ball bearings for smoother rolling with less effort and maintenance
- Trolley Range from 0.5t to 10.0t
- The 5:1 factor of safety allows for use with manual or powered hoists

These units meet and exceed all the requirements within BS EN 13157: 2004+A1:2009 and AS1418.2.

**Certification:**

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC.

**Technical Data**

Product Code	Capacity (tonne)	A Track width range (mm)	Dimensions (mm)					Min. curve ratio (m)	Mass (kg)
			B	C	D	E	F		
APT-0050	0.5								
APT-0100	1.0	75-210	391	83.5	16	110	81	1.0	9.6
APT-0200	2.0	75-210	391	94.5	18	123	89	1.3	13.5
APT-0300	3.0	75-210	403	105.5	22	141	112		
APT-0600	6.0	105-305	521	111	27	151.5	125		
APT-1000	10.0								

Further dimensions to be advised soon.

**Technical Drawings**

