

Air Wheel Grinders and Cutting Tools

NEW

345MAX-M
Ø 125 mm (5 in)
3445MAX-M
Ø 115 mm (4.5 in)

- 0.66 kW (0.88 HP).
- 12 000 rpm.
- Speed governor.
- Composite housing.
- Piped-away exhaust system.



3445MAX-M













LA422-EU - Ø 125 mm (5 in)
LA421-EU - Ø 100 mm (4 in)

- 0.50 kW (0.65 HP).
- 12 000 rpm.



LA422-EU

Specifications at 6.2 bar (90 psi)

	CPN												
		mm	M14	kW	rpm	kg	mm	NPTF	mm	L/s	L/s	dB(A)	m/s ² / K ⁽¹⁾
345MAX-M	45664257	125	M14	0.66	12 000	1.56	245	1/4"	10	4.9	19.3	79.6	7.9 / 0.7
3445MAX-M	45664240	115	M14	0.66	12 000	1.53	245	1/4"	10	4.9	19.3	79.6	6.4 / 2.0
LA422-EU	01328582	125	3/8"-24	0.50	12 000	1.75	229	1/4"	10	2.8	10.4	85.6	6.0 / 2.1
LA421-EU	01328632	100	3/8"-24	0.50	12 000	1.75	229	1/4"	10	2.8	10.4	85.6	4.8 / 1.4

(1) ISO28927 – 3-axis measurement: vibration level / measurement uncertainty.

NEW

529

- Stroke: 10 mm (0.4 in).
- 9 500 strokes per minute.
- Only 0.54 kg.
- Variable speed lever.
- 360° adjustable exhaust.
- Contains: blades (6 pieces).



7802SA

- Cutting capacity: 1.0 mm (20-gauge, 0.04 in).
- 4 200 blows per minute.

4429

- Stroke: 10 mm (0.4 in).
- 5 000 strokes per minute.
- Variable speed lever.
- Piped-away exhaust system.

Accessories: **P4FS-6** (CPN: 45525474): blades, 12 teeth/cm (6 pieces).

P4CS-6 (CPN: 45525508): blades, 10 teeth/cm (6 pieces).


NEW

325B

- Cutting capacity: 1.2 mm (18-gauge, 0.05 in).
- 4 200 blows per minute.
- Variable speed lever.













Available blades:



LA418A-EU

- 8 000 strokes per minute.
- Variable speed lever.
- Piped-away exhaust system.
- Supplied without blades.

Specifications at 6.2 bar (90 psi)

	CPN										
		1 min.	mm	kg	mm	NPTF	mm	L/s	L/s	dB(A)	m/s ² / K ⁽¹⁾
4429	01371822	5 000	10 mm	0.74	234	1/4"	6	1.9	3.6	66.2 ⁽²⁾	9.5 / 2.4
529	47125885	9 500	10 mm	0.70	246	1/4"	6	0.5	0.5	84.3	3.1 / 1.0
325B	49806568	4 200	–	0.95	185	1/4"	10	1.9	8.0	96.0	15.9 / 1.9
7802SA	80113681	4 200	–	1.27	239	1/4"	10	1.9	9.9	83.0	3.0 / 1.0
LA418A-EU	01336353	20 000	3°	1.00	208	1/4"	10	1.8	12.3	90.8 ⁽²⁾	6.7 / 2.5

(1) ISO28927 – 3-axis measurement: vibration level / measurement uncertainty — (2) Piped-away exhaust system.