

Cordless Ratchets

R385 – 1/2"
Tool only

R385-2L
1/2" - Kit

R380 – 3/8"
Tool only

R380-2L
3/8" - Kit

- 95 Nm (70 ft-lb).
- 225 rpm.
- 14.4 V.
- Variable speed lever.

Accessories: **107-BOOT** (CPN: 45505328), protective tool boot.



R145 – 3/8"
Tool only

R145-2L
3/8" - Kit

R140 – 1/4"
Tool only

R140-2L
1/4" - Kit

- 34 Nm (25 ft-lb).
- 225 rpm.
- 7.2 V.
- Variable speed lever.

Accessories: **103-BOOT** (CPN: 45505310), protective tool boot.



Impact Socket Sets

SK2M12 (CPN: 81287336): 1/4" socket set (6, 7, 8, 9, 10, 11, 12, 13 and 14 mm, 50 and 100 mm extensions).

SK3M10 (CPN: 81287344): 3/8" socket set (9, 10, 11, 12, 13, 14, 15, 16, 17 and 19 mm).

SK4M14 (CPN: 81287351): 1/2" socket set (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm).

	CPN Tool only	CPN Kit	V	Nm	Max. Nm	1 min. rpm	kg	mm	dB(A)	m/s ² / K ⁽¹⁾
1/2" <input type="checkbox"/>										
R385	45498839	17016239	14.4	14-81	95	225	1.90	315	80.8	4.9 / 0.9
3/8" <input type="checkbox"/>										
R380	45498821	17016338	14.4	14-81	95	225	1.90	315	80.8	4.9 / 0.9
R145	45498854	17016312	7.2	7-34	34	225	1.30	272	74.9	< 2.5
1/4" <input type="checkbox"/>										
R140	45498847	17016270	7.2	7-34	34	225	1.30	272	74.9	< 2.5

(1) ISO28927 – 3-axis measurement: vibration level / measurement uncertainty.

Cordless Drills

D650S
Tool only

D650S-2L - Kit

- Keyless chuck: 13 mm (1/2 in).
- 73 Nm (650 in-lb).
- 19.2 V.
- 17-position clutch.
- 2 speeds: 360 and 1 300 rpm.
- 1-hand forward and reverse switch.



D550S
Tool only

D550S-2L - Kit

- Keyless chuck: 13 mm (1/2 in).
- 62 Nm (550 in-lb).
- 14.4 V.
- 17-position clutch.
- 2 speeds: 360 and 1 300 rpm.
- 1-hand forward and reverse switch.



1.15 kg,
176 mm

D040 – Tool only
D040-2L - Kit

- Standard chuck: 6.5 mm (1/4 in).
- 4.5 Nm (40 in-lb).
- 7.2 V.
- 1 100 rpm.
- 1-hand forward and reverse switch.



	CPN Tool only	CPN Kit	V	Max. Nm	1 min. rpm	kg	mm	dB(A)	m/s ² / K ⁽¹⁾
Keyless chuck: 13 mm (1/2 in)									
D650S	45651767	17024985	19.2	74	360 / 1 300	2.10	244	70.8	< 2.5
D550S	45651478	17025750	14.4	62	360 / 1 300	2.05	244	76.1	< 2.5
Standard chuck: 6.5 mm (1/4 in)									
D040	45518230	24930257	7.2	4.5	1 100	1.15	176	63.4	< 2.5

(1) ISO28927 – 3-axis measurement: vibration level / measurement uncertainty.